## SUPERCAPACITOR/SUPERCONDENSATEUR ESCap 10/42

VOLTAGE 42 V

CAPACITANCE 11 F

POWER MAX 2.6 kW

ENERGY 10 kJ @ 42 V

RESISTANCE [ESR] 0.17 Ohm

TEMPERATURE -40 to +55 °C

WEIGHT 10.5 kg

DIMENSIONS Dia 230 x 110 mm



## RECOMMENDED APPLICATIONS FOR THIS SUPER CAPACITOR:

- -42-VOLT AUTOMOTIVE SYSTEMS
- -STOP/START AUTOMOTIVE SYSTEMS

The supercapacitors are manufactured and tested in compliance with the following standards or portions thereof: CSA C22.1 Canadian Electrical Code, Part 1 – Safety Standard for Electrical Installations 2002; CSA C22.2 Canadian Electrical Code, Part 2 – General Requirements – 2002; CSA C22.2 No 107 General Use Power Supplies – 2001; CSA C22.2 No 94 Special purpose Enclosures – 2001; CSA/ASME Boiler Pressure Vessels – Section 8 – Rules for Construction of Pressure vessels – Division 2 – Alternative Rules – 2001; NFPA 30 Flammable and Combustible liquids Code – 2000.