## SUPERCAPACITOR/SUPERCONDENSATEUR ESCap 6/14

VOLTAGE 12 V

CAPACITANCE 153 F

POWER MAX 2.4 kW

ENERGY 6 kJ @ 14 V

[ESR] 0.01 Ohm

TEMPERATURE -40 to +55 °C

WEIGHT 38 kg

DIMENSIONS Dia 230 x 100 mm



## RECOMMENDED APPLICATIONS FOR THIS SUPER CAPACITOR:

- 12-VOLT AUTOMOTIVE SYSTEMS STARTING ENGINES UP TO 1.5L
- STOP/START AUTOMOTIVE SYSTEMS

The supercapacitors are manufactured and tested in compliance with the following standards or portions thereof: CSA C22.1. Canadian Electrical Code, Part 1 – Safety Standard for Electrical Installations 2002; CSA C22.2 Canadian Electrical Code, Part 2 – General Requirements – 2002; CSA C22.2 No 107 General Use Power Supplies – 2001; CSA C22.2 No 94 Special purpose Enclosures – 2001; CSA/ASME Boiler Pressure Vessels – Section 8 – Rules for Construction of Pressure vessels –Division 2 – Alternative Rules – 2001; NFPA 30 Flammable and Combustible liquids Code – 2000.